

RMG SERIES

Medium-high speed washer
Hard-mount structure



Robustness, durability and profitability

Robust, profitable design . Made using the finest materials to ensure long life and fast payback.

Intensive washing and care for linen

The Care Touch system and advanced controls ensure meticulous care of linen. High quality finishes for linen, prolonging items' life by caring for fibres.

A control to meet every need

Choose from a wide range of fully-equipped controls to meet every need

- **Logi PRO:** up to 25 programmes / 11 phases, with 6 selectable water levels and 4 dosing signals.
- **Coin** for vended laundries, 4 fully configurable programmes.
- **Profit Plus** for vended laundries, 4 fully configurable programmes plus 3 extra options to boost revenue.

Aqua Fall

Water consumption is minimised thanks to the design of the perforated blades in the drum, creating a cascade effect. More washing action with less water, making it possible to shorten cycle time and save water.

Aqua Mixer

High-precision water temperature control system (+/- 1°C) throughout the cycle. In washing machines with internal heating the temperature can be maintained. Excellent for the most demanding processes, such as disinfection.



- Online laundry management platform to monitor and control Girbau machines remotely.
- Allows you to cut laundry costs and boost your business.
- To find out more visit: sapphire.girbau.com



Dry linen capacity 1/9	kg 1/9 (lb)	18.4 (40.5)
Dry linen capacity 1/10	kg 1/10 (lb)	16.56 (36.5)
Drum Volume	dm ³ (cu ft)	165.6 (5.85)
Drum diameter	mm (in)	620 (24.4)
Drum length	mm (in)	549 (21.6)
Static force transmitted	kg (lb)	365 (805)
Dynamic force transmitted	kg (lb)	829 (1,828)
Frequency of the dynamic force	Hz	12.7
Kinetic energy	N*m	21,100
Sound level	dbA	70

Machine dimensions

(L) Width	mm (in)	750 (29.5)
(P) Depth	mm (in)	1,063 (41.9)
(H) Height	mm (in)	1,344 (52.9)
Weight	kg (lb)	255 (562)
Diameter of loading opening	mm (in)	327 (12.9)
(h) Height from door base to floor	mm (in)	509 (20)

Dimensions with packaging

Width	mm (in)	777 (30.6)
Depth	mm (in)	1,095 (43.1)
Height	mm (in)	1,494 (58.8)
Weight	kg (lb)	283 (624)

Motor power capacity

Washing	kVA	0.6
Spinning	kVA	0.8

Speeds

Washing	rpm	47
Spinning	rpm	760
G Force		200

CONNECTIONS

(A) Hot water (AF) Cold Water

Connection Ø	in	3/4
Recommended pressure	bar (psi)	0.5-6 (7-87)
Flow rate (4 bar)	l/min(USgal/min)	60 (16)
Maximum temperature	°C (°F)	80 (176)

(D) Drain

Gravity drain Ø	in	3
Flow rate	l/min(USgal/min)	130 (34.3)

(V) Steam

Connection	in	1/2
Recommended pressure	bar (psi)	2-6 (29-87)
Flow rate	kg/h (lb/h)	60 (132)

(d) External dosing

Connection Ø	in	3/8
--------------	----	-----

(E) Electricity

Electric heated

Nominal voltage	Hz	Heating power kW	Total power kW	Switch A
200-240V	50/60Hz 1ph	6 / 10	6.6 / 10.6	40 / 63
200-240V	50/60Hz 3ph	9 / 15	9.6 / 15.6	32 / 50
380-415V	50/60Hz 3ph	9 / 15	9.7 / 15.7	20 / 32

Steam heating or without heating

200-240V	50/60Hz 1ph	-	0.8	6
----------	-------------	---	-----	---

*Specifications subject to change without prior notice or obligation

